Form 3160-5 (August 1999)		TED STATES	D	FORM APPROVED CS
		F LAND MANAGEMEN	іт ОІ	OMB No. 1004-0135 Expires November 30, 2000
	SUNDRY NOTICE	S AND REPORTS ON	WELLS N.M. I	DIV-DIST. 2
	Do not use this form fo	or proposals to drill or to	re-enter an 1301 W. (Grandwawsprue
	abandoned well. Use Fo	orm 3160-3 (APD) for suc	^{ch proposals.} Artesia,	
				7. If Unit or CA/Agreement, Name and/or No.
Type of Well	UBMIT IN TRIPLICATE	- Other Instructions on re	everse side	SRM 1150 8. Well Name and No.
Oil Well	Gas Well	Other	Injection	BOX CANYON UNIT #2
Name of Operator		/	123450/09/0	
Yates Petroleum C	Corporation /		1013 1013	
	Artesia, NM 88210	3b. Phone No. (inclue 505-748-1471	SEP 2002	いして、Field and Pool, or Exploratory Area
Location of Well (Footage, S			RECEIVED	MORROW
080' FNL & 1980' FV	VL Section 13-	-T21S-R21E	OCD - ARTESIA	5/
12. CHECK APP	ROPRIATE BOX(ES) TO	DINDICATE NATURE OF	NOTICE, REPORT, OR OTHE	
PE OF SUBMISSION			TYPE OF ACTION	
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	Other
i mai Abandonment Notice				
n mai Abandonment Notice	Change Plans	X Plug and Abandon	Temporarily Abandon	
Describe Proposed or Completer directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r	Change Plans Convert to Injection Operation (clearly state all pertin ontally, give subsurface locations ith BLM/BIA. Required subseque new interval, a Form 3160-4 shall	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of I be filed once testing has been co	Water Disposal tarling date of any proposed work and agepths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices st	pproximate duration thereof. If the proposal is to deepen Attach the Bond under which the work will be performed d operations. If the operations results in a multiple halt be filed only after all requirements, including
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w	Change Plans Convert to Injection Operation (clearly state all pertinontally, give subsurface locations in BLM/BIA. Required subseque new interval, a Form 3160-4 shall id, and the operator has determin	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of I be filed once testing has been co led that the site is ready for final in	Water Disposal tarting date of any proposed work and ag apths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.)	. Attach the Bond under which the work will be performed d operations. If the operations results in a multiple
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475	Change Plans Convert to Injection Operation (clearly state all pertir ontally, give subsurface locations ith BLM/BIA. Required subseque new interval, a Form 3160-4 shall d, and the operator has determin top. thubing @ 6480'. Dumpe n top. mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5, '. WOC.	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s	Water Disposal tarting date of any proposed work and an epiths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including t CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @	Change Plans Convert to Injection Operation (clearly state all pertir initially, give subsurface locations in BLM/BIA. Required subseque iew interval, a Form 3160-4 shall id, and the operator has determin the operator has determined to use the operator has dete	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s	Water Disposal tarting date of any proposed work and an epiths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including t CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market	Change Plans Convert to Injection Operation (clearly state all pertii ontally, give subsurface locations ith BLM/BIA. Required subseque iew interval, a Form 3160-4 shall id, and the operator has determin if tubing @ 6480'. Dumpe in top. if mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5. '. WOC. 876'. Spot 40 sx Class "Cer.	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co ued that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258	Water Disposal tarting date of any proposed work and ag epths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg 8'. Circulate 20 sx Class "C" Ne	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including t CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market	Change Plans Convert to Injection Operation (clearly state all pertii ontally, give subsurface locations ith BLM/BIA. Required subseque iew interval, a Form 3160-4 shall d, and the operator has determin the ubing @ 6480'. Dumpe in top. much laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5. '. WOC. 876'. Spot 40 sx Class "Cert.	X Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of 1 be filed once testing has been co- ued that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258 Approved as to plugging Liability under bood to a	Water Disposal tarting date of any proposed work and ag- appths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices st ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg 8'. Circulate 20 sx Class "C" Ne of the wet totals.	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including the CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED
Describe Proposed or Completer directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole marke	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque lew interval, a Form 3160-4 shall d, and the operator has determin t/ tubing @ 6480'. Dumpe in top. // mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5, '. WOC. 876'. Spot 40 sx Class "C er.	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co ued that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258	Water Disposal tarting date of any proposed work and ag- appths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices st ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg 8'. Circulate 20 sx Class "C" Ne of the wet totals.	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including t CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install
Describe Proposed or Completer directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole marker	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque lew interval, a Form 3160-4 shall d, and the operator has determin t/ tubing @ 6480'. Dumpe in top. // mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5, '. WOC. 876'. Spot 40 sx Class "C er.	X Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of 1 be filed once testing has been co- ued that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258 Approved as to plugging Liability under bood to a	Water Disposal tarting date of any proposed work and ag- appths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices st ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg 8'. Circulate 20 sx Class "C" Ne of the wet totals.	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including the CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 2002
Describe Proposed or Completer directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market C	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque lew interval, a Form 3160-4 shall d, and the operator has determin t/ tubing @ 6480'. Dumpe in top. // mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5, '. WOC. 876'. Spot 40 sx Class "C er.	X Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of 1 be filed once testing has been co- ued that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258 Approved as to plugging Liability under bood to a	Water Disposal tarting date of any proposed work and ag apths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg B'. Circulate 20 sx Class "C" Ne of the well there. stained until mpleted.	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including the CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 2002 LES BABYAK
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market w l hereby certify that the foregoing Name (Printed/Typed) Donna Clack	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque lew interval, a Form 3160-4 shall d, and the operator has determin t/ tubing @ 6480'. Dumpe in top. // mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5, '. WOC. 876'. Spot 40 sx Class "C er.	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-256 Approved as to plugging lability under bond is re surface restoration is col	Water Disposal tarting date of any proposed work and ag apths of all pertinent markers and zones. days following completion of the involved impleted. Final Abandonment Notices sh ispecition.) eat cement on top of CICR. Set tub @ 1594'. WOC 4 hrs. Tagg 8'. Circulate 20 sx Class "C" Ne of the well bytice. stained until metated. Title	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including at CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 2000
Describe Proposed or Completed directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market w l hereby certify that the foregoing Name (Printed/Typed) Donna Clack	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque new interval, a Form 3160-4 shall d, and the operator has determin the operator has determine the operator has d	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-256 Approved as to plugging lability under bond is re surface restoration is col	Water Disposal Water Disposed work and ap path of all pertinent markers and zones. Water Dispetition.) Water Disposed work and ap Water Dispetition Water Disposed work and ap Water Dispetition Wa	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including at CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 200 LES BABYAK IM PETROLEUM ENGINEER
Describe Proposed or Complete directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market w lhereby certify that the foregoing Name (Printed/Typed) Donna Clack Signature	Change Plans Convert to Injection Operation (clearly state all pertin initially, give subsurface locations ith BLM/BIA. Required subseque new interval, a Form 3160-4 shall d, and the operator has determin the operator has determine the operator has d	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-256 Approved as to plugging lability under bond is re surface restoration is col	Water Disposal Water Disposal Water Disposal Water Disposal Water Disposal Water Disposed work and ag posts of all pertinent markers and zones. Date Constraints of all pertinent markers and zones. Water Dispection of the involved water Dispection of the involved water Dispection.) Water Disposed work and ag post of the well build. Build Dispect Dispections Technicit Date 8-28-02	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple half be filed only after all requirements, including at CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 200 LES BABYAK IM PETROLEUM ENGINEER
Describe Proposed or Completer directionally or recomplete horizo or provide the Bond No. an file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Clas 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Clas "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market Line Line Line Line Line Line Line Line	Change Plans Convert to Injection Convert to Injection Operation (clearly state all pertii ontally, give subsurface locations th BLM/BIA. Required subseque tew interval, a Form 3160-4 shall d, and the operator has determin top. thubing @ 6480'. Dumpe n top. mud laden fluid. s "C" Neat cement @ 350 416' 5-1/2" casing. s "C" Neat cement @ 8-5. '. WOC. 876'. Spot 40 sx Class "C" tr. thubing @ 6480'. Class "C" to true and correct	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of l be filed once testing has been co led that the site is ready for final in ad bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258 POProved as to plugging Lability under bond is re surface restoration is cop THIS SPACE FOR FEDE	Water Disposal Water Disposal Water Disposal Water Disposal Water Disposed work and ag paths of all pertinent markers and zones. Stays following completion of the involved Impleted. Final Abandonment Notices st respection.) Water Disposal Water Disposed work and ag tub @ 1594'. WOC 4 hrs. Tagg B'. Circulate 20 sx Class "C" Ne of the well twices tained until mpleted Title Operations Technicit Date 8-28-02 CRAL OR STATE OFFICE USE	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple nall be filed only after all requirements, including at CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 200 LES BABYAK an PETROLEUM ENGINEER
Describe Proposed or Complete directionally or recomplete horizo or provide the Bond No. on file w completion or recompletion in a r reclamation, have been complete 1-17-02- Tagged CICR w Class "C" Neat cement o 1-18-02- Circulate hole w 1-22-02- Spot 25 sk Class 1-23-02- Cut & POH w/ 1 1-24-02- Spot 50 sx Class "C" Neat cement @ 1475 1-25-02- Tagged plug @ regulation dry hole market w? I hereby certify that the foregoing Name (Printed/Typed) Doma Clack Signature Conditions of approval, if any, are the applicant to conduct operations the applicant to conduct operations the	Change Plans Convert to Injection Convert to Injection Operation (clearly state all pertii ontally, give subsurface locations ith BLM/BIA. Required subseque new interval, a Form 3160-4 shall d, and the operator has determin the tubing @ 6480'. Dumpe in top. the much and the operator has determin the tubing @ 6480'. Dumpe in top. the much and the operator has determin the tubing @ 6480'. Dumpe in top. the much and the operator has determin the tubing @ 6480'. Dumpe in top. the much and the operator has determin the operator has determine the operator operator has determine the operator op	Plug and Abandon Plug Back nent details, including estimated si and measured and true vertical de ent reports shall be filed within 30 of 1 be filed once testing has been co led that the site is ready for final in ed bailed 5 sx Class "C" Ne 00 to 3253'. /8" shoe & 5-1/2" casing s C" Neat cement @ 405-258 Poproved as to plugging Hability under bond is re surface restoration is cop THIS SPACE FOR FEDE Coos not warrant or certify that lect lease which would entitle tree	Water Disposal Water Disposal Water Disposal Water Disposal Water Disposed work and ag paths of all pertinent markers and zones. Stays following completion of the involved specifion.) Water Disposal work and ag water Disposed work and ag tub @ 1594'. WOC 4 hrs. Tagg B'. Circulate 20 sx Class "C" Ne of the well twices the displayed of the well twices Date 8-28-02 CRAL OR STATE OFFICE USE Title Office	Attach the Bond under which the work will be performed d operations. If the operations results in a multiple nall be filed only after all requirements, including at CIBP @ 5918'. Dumped bailed 5 sx ged plug @ 1473'. Spot 30 sx Class eat cement from 60' to surface. Install APPROVED SEP - 5 200 LES BABYAK an PETROLEUM ENGINEER