

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

FEB 4 1976

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-5230
7. Unit Agreement Name Big Eddy Unit
8. Farm or Lease Name Big Eddy Unit
9. Well No. 45
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT PERIOD  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Perry R. Bass
3. Address of Operator P. O. Box 2760 Midland, TX 79701
4. Location of Well UNIT LETTER <u>H</u> , <u>1880</u> FEET FROM THE <u>N</u> LINE AND <u>790</u> FEET FROM THE <u>E</u> LINE, SECTION <u>16</u> TOWNSHIP <u>21-S</u> RANGE <u>30-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3306' Gr, Graded 3303', KB 3315'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-18-76: With DP at 1023' ran 300 sks Class C cement. Estimated top of plug at 510' WOC 5½ hrs. Tagged mushy cement at 775'. Pulled out of hole with plugged drill pipe (372'). WOC additional 5 hrs - went in hole to base of surface casing (468') - circulated with partial returns - recovered wet cement. Spotted 50 sks Class C cement with bottom at 464' - top of plug should be at 364'. WOC 5 hrs - tagged solid cement at 454'. Spotted additional 50 sks from 454' to 350'. Surface plug and marker not yet installed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. P. Foster W. P. Foster

TITLE Senior Petroleum Engineer

DATE February 3, 1976.

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: