

13 3/8-602-525 BX
9 5/8-2991-1459 BX
5 1/2-11,425-575 BX
2 3/8-10,962

IP (Morrow) Perf# (11,000-140) CAOF 1917 MCF/GPD. GOR Dry; gtv
(Gas) .702; SGRHP 3000; SGRHP 3103

3417 GL

sub-9

FLARE # 11, 118-140 GWO
PD 11, 118-140 (Morrow)
(Orig. emp 4-23-77 thru (Morrow) Perfs 10,377-
379; OPR 11,175; OPB 10,865)
TD 11,425; PED 11,175; Complete
Acid (10,377-379) 1500 gals
Swbd dry w/10 IN flare (10,377-379)
Gnt ref 11,175
Sgzd (10,377-379) 100 sx
DOC & set GIBB # 11,175 to re-open old perfs
11,018-140
Flare # 11, 118-140) 20,000 gals gel + 20,350# sd
(Morrow) FOUR POINT GAUGES:
Flare 207 ROTATED, chk (NR), 60 mins TP 2945
Flare 521 ROTATED, chk (NR), 60 mins, TP 2800
Flare 522 ROTATED, chk (NR), 60 mins TP 2530
Flare 523 ROTATED, chk (NR), 60 mins, TP 2180
Flare 524 ROTATED, 10,062

1-4-55 NM

39-015-70011-37