

(November 1983)
(Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

PERMIT IN TRIPPLICATE
(Other Instructions on Reverse Side)

BLM Form No. 1001-01
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

IF INDIAN, ALLOTTEE OR TRIBE NAME

FEB 13 8 52 AM '89

CARLISBAD
ARM OR LEASE NAME
Government ABRS

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Undes. Burton Flats Atoka, N.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9 T20S R28E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

RECEIVED

FEB 24 '89

O. C. D.
ARTESIA, OFFICE

OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR

OXY USA INC

3. ADDRESS OF OPERATOR

P. O. Box 50250, Midland, TX 79710

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2105' FSL 760' FWL Sec. 9, T20S, R28E,
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

3282.7

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Well Completion Data

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

T.D. 11290' P.B.T.D. 10920' SI pending test of Morrow zone.

MIRU completion unit, ND WH NU BOP POOH w/tbg, RIH w/Kutrite shoe, packer picker and
DC's on 2-7/8" tbg and mill out packer @ 9725'. RIH w/5-1/2" Cem. Ret. Set @ 9704',
squeeze Canyon perfs (9811'-9845') w/100 sx CL. H w/.6% Halad-9. RIH w/5-1/2" Cem.
Ret. set @ 9212' and @ 8907', squeeze Wolfcamp perfs (9294'-9344' & 9003'-9023')
w/a total of 200 sx. CL. H w/.6% HALAD-9 and 100 sx CL. H neat. Drill out cement, test
csg. 1500# - Held OK. Perf. Atoka w/2 SPF @ 10406', 07', 08', 09', 10', 11', 12', 14',
15', 16', 17', 18', 19', 20', 21', 10696', 97', 98', 10705', 06', 07', 08', 71', 72', 73',
74', 75', 76', 78', 79', 98', 99', 10800'. Total of 66 holes (.45" entrance hole 14.7"
penetration in Berea). RIH w/2-7/8" tbg. 1.87 Mod. F PROF. NIP. and Pkr, set Pkr @
10295' Drop bar broke DISC, slight show of Gas, RU SWAB, no fluid in hole. Acidize
Atoka perfs (10406'-10800') w/5000 gal. 7-1/2% NeFe HCL w/Fric. Red, Clay stab and 1000
SCF N₂/Bbl. Max pres. 5300#, Min pres. 4600#, Avg. Pres. 4900', ISIP 4100#, 5 min 3700#,
10 min. 3600#, 115 min. 3570#. Flowed 39 BLW in 6 Hrs on choke 1" FTP 3700# to 20#.
14 SITP 2750#, 5 WBD. well, Rec 0 BO 77 BLW install 2" orif. tester flow well as follows:

(Continued on Attached Sheet)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Oper. Mgr.

DATE 2-8-89

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

FEB 22 1989

*See Instructions on Reverse Side

SSS

CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the
United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.