

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

copy to SF

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

0354232

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Elizondo Federal "A"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Und. Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 37, T-21-S, R-27E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Cities Service Oil Company

MAY 19 1977

3. ADDRESS OF OPERATOR

P. O. Box 1919, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

1780' FSL, 2180' FWL, Section 34, T-21-S, R-27-E,
Eddy County, New Mexico.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3142.9' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3000', Lime. Preparing to drill ahead.

Drilled to 3000' and set 15 jts. (619.96') of 8-5/8" OD, 32#, 8R, K55, ST&C casing and 57 jts. (2357.24') of 8-5/8" OD, 24#, 8R, K55, ST&C casing set at 3000' and cemented with 300 sacks of thick set w/12# Gilsonite, 1/4# Flocele & 2% CaCl followed by 1000 sacks Halco Lite w/5# Gilsonite & 1/4# Flocele followed by 300 sacks Class C w/2% CaCl. Plugdown at 0455 MDT, 5/6/77. Cement circulated. WOC 12 hours. Tested casing to 1500# - ok.

RECEIVED

MAY 18 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operations Manager

DATE 5/13/77

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE MAY 18 1977

CONDITIONS OF APPROVAL, IF ANY: