



July 20, 1995

ELIZONDO FEDERAL A #5

Current Configuration
Elevation: 17' KB-GL

1780' FSL & 2180' FWL
Sec 34 T21S R27E
Eddy Co., New Mexico

Tubing: (Top to Bottom)

377 jts 2-7/8", 6.5#, N-80 8rd
Otis on-off tool w/2.3" profile nipple
Otis Perma Latch pkr

13-3/8", 54.5#, K-55 ST&C
Set @ 605'
Cmt'd w/850 sx-circ'd 10 sx to pit

FISH: Tbg Conveyed
Perf Gun:
OD: 3.38" ID: 2.25"
Length: 46.41'

8-5/8", 24 & 32#, K-55 ST&C
Set @ 3000'
Cmt'd w/1600 sx - circ'd to surface

TOC @ 8400' (Temp Svy)

Wolfcamp Perfs: (Sqz'd)
9,579', 81', 83', 85'

5-1/2" XO @ 9,785'
17# above & 20# below

Morrow Perfs: (OLD)
11,406', 19-21', 26-28', 31', 36-40',
11,444-47', 11,500-10', 49', 54-68'

Otis on-off tool w/2.3 profile nipple
Set @ 11,633'
2-7/8" X 5-1/2" Otis Perma Latch pkr
Set @ 11,634'

Morrow Perfs: (NEW)
11,755-61'

Abandoned Morrow Perfs:
11,807-09'

Prepared By: Brian Singletary

New PBTD: 11,800'
CIBP @ 11,800'

5-1/2", 17 & 20#, N-80
Set @ 11,830'
Cmt'd w/750 sx

Original PBTD: 11,820'
TD: 11,830'

