



COMPUTERIZED DATA ANALYSIS

APRIL 5, 1977

GENTLEMEN:

THE ENCLOSED TEST APPEARS TO BE A GOOD MECHANICAL DRILL STEM TEST DURING WHICH THE TOOLS DID FUNCTION PROPERLY. THE FORMATION PRODUCED ENOUGH RESERVOIR FLUID FOR PROPER IDENTIFICATION. RESERVOIR PRESSURE DRAWDOWN WAS SUFFICIENT AND ADEQUATE SHUT-IN BUILD-UPS DID OCCUR FOR RELIABLE QUANTITATIVE ANALYSIS. RESERVOIR PARAMETERS WERE CALCULATED BY THE MCKINLEY METHOD.

1. FLOW RATE: A FLOW RATE OF 220 MCF/DAY OF GAS WAS NOTED DURING THIS TEST.
2. RESERVOIR PRESSURE: EXTRAPOLATION OF THE INITIAL SHUT-IN PRESSURE BUILD-UP INDICATES A MAXIMUM RESERVOIR PRESSURE OF 4280 P.S.I.G. AT RECORDER DEPTH. EXTRAPOLATION OF THE FINAL SHUT-IN PRESSURE BUILD-UP INDICATES A MAXIMUM RESERVOIR PRESSURE OF 3600 P.S.I.G. AT RECORDER DEPTH. THE DIFFERENCE BETWEEN THE INITIAL AND FINAL SHUT-IN PRESSURE OF 680 P.S.I.G. IS INDICATIVE OF DEPLETION. A LIMITED RESERVOIR IS PRESENT IF DEPLETION IS ACTUALLY TAKING PLACE.
3. PERMEABILITY: THE CALCULATED TRANSMISSIBILITY FACTOR OF 9.50 MD.-FT./CP. INDICATES AN AVERAGE EFFECTIVE PERMEABILITY TO GAS OF 0.04 MD. FOR THE REPORTED 6 FOOT NET INTERVAL. THE CALCULATIONS WERE BASED ON A MCKINLEY SLOPE OF 4082 P.S.I./LOG CYCLE OBTAINED FROM THE FINAL SHUT-IN BUILD-UP PLOT. IT WAS ASSUMED FOR THESE CALCULATIONS: (A) GAS GRAVITY 0.70 (B) VISCOSITY .025 CP. (C) AND GAS DEVIATION FACTOR 0.82. THESE FIGURES WERE OBTAINED FROM THE AVAILABLE TECHNICAL LITERATURE.
4. WELL BORE DAMAGE: THE CALCULATED DAMAGE RATIO OF 0.42 INDICATES THAT A STIMULATED WELL BORE IS PRESENT AT THE TIME AND CONDITIONS OF THIS TEST.
5. RADIUS OF INVESTIGATION: THE CALCULATED RADIUS OF INVESTIGATION OF THIS TEST IS 7 FEET BASED ON AN ASSUMED POROSITY OF 10%, COMPRESSIBILITY OF 4.2×10^{-4} , AND OTHER ASSUMPTIONS MADE IN NUMBER 3 ABOVE.
6. GENERAL COMMENTS: THE FORMATION EXHIBITS THE CHARACTERISTICS OF RELATIVELY LOW PERMEABILITY EFFECTIVE TO THE RESERVOIR FLUID AND INDICATES THE ABSENCE OF WELL BORE DAMAGE. BOTH THE MCKINLEY AND HORNER PLOTS SHOW A DECREASE IN TRANSMISSIBILITY AWAY FROM THE WELL BORE WHICH INDICATES A STIMULATED WELL BORE. IF THIS CONDITION IS PRESENT, THE FLOW RATE WOULD DECREASE TO 73 MCF/DAY.

Kent Arceneaux
KENT ARCENEUX
RESERVOIR EVALUATION
DEPARTMENT

LARIO OIL & GAS COMPANY
STATE "F" #1; EDDY COUNTY, NEW MEXICO
TEST #2; 9533' TO 9585'

FIELD REPORT #15163 C

In making any interpretation, our employees will give Customer the benefit of their best judgment as to the correct interpretation. Nevertheless, since all interpretations are opinions based on inferences from electrical, mechanical or other measurements, we cannot, and do not guarantee the accuracy or correctness of any interpretations, and we shall not be liable or responsible, except in the case of gross or wilful negligence on our part, for any loss, costs, damages or expenses incurred or sustained by Customer resulting from any interpretation made by