

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. O. C. C. ONLY
SUBMIT IN TRIPL
(Other Instructions
verse side)Form approved
Budget Bureau No. 42-R1421.

5. LEASE DESIGNATION AND SERIAL NO.

NM 5489

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Maralo HL Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

E. Burton Flat
Wildcat11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12-20S-28E

Unit I NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a well. For such proposals, use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ JUL 25 19772. NAME OF OPERATOR
Yates Petroleum Corporation3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 882104. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FSL & 660' FEL of Section 12-20S-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3264' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set Prod. Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 11700' - Ran 367 joints of 4½" N-80 casing as follows: 19 joints 13.5# N-80 (598'), 318 joints 11.6# N-80 (10114'), 30 joints 13.5# N-80 (943') set at 11655'. Diff-fill shoe at 11655', diff-fill collar at 11624'. Centralizers at 11590, 11493, 11395, 11303 and 11240'. Cemented by Halliburton w/480 sacks of Class H + .5% CFR-2 + 4#/sack KCL. PD 1:00 PM 5-12-77. Pressure tested to 2000#. OK. WOC and Ran Temperature Survey, found top of cement at 9980'. WLPBTD 11600'.

RECEIVED

JUL 01 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE

Geol. Secty

DATE

7-1-77

(This space for Federal or State office use)

APPROVED BY

Lee D. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 22 1977

CONDITIONS OF APPROVAL, IF ANY: