

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
STATE	✓
FEDERAL	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	✓

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

MAY 16 1977

O.C.C.

ANTHONY OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-5100 & L-6223	
7. Unit Agreement Name	

8. Farm or Lease Name	
W. R. State Com.	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
Burton Flat Morrow	
12. County	
Eddy	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Read & Stevens, Inc.
3. Address of Operator
P. O. Box 2126, Roswell, New Mexico 88201
4. Location of Well
UNIT LETTER <u>XX</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>21S</u> RANGE <u>27E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3207' GR - 3222' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	

TD 11,470', PB 11,380'. Drilled 7 7/8" hole from 2,600' to 11,470'. Ran 300 joints 5 1/2", 17# & 20#, N-80, L. T. & C. casing, total of 11,485.01', set at 11,470' RKB. Cemented with 700 sx. Class "H" cement with 3/4 of 1% CFR-2 & 5# KCL per sx. Plug down @ 4:15 P. M., 5-7-77. Tested casing to 3,500# for 30 min., rel. press. & float held OK. Ran temperature survey with cement top @ 7740' RKB. Tagged cement plug @ 11,380'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Agent DATE May 11, 1977

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE MAY 17 1977

CONDITIONS OF APPROVAL, IF ANY: