

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

MAR 2 1979

O. C. C.
ARTESIA OFFICE

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-5100 & L-6223

SUNDARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - 1 (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐	GAS WELL ☒	OTHER ☐	7. Unit Agreement Name
Name of Operator			8. Farm or Lease Name
Read & Stevens, Inc. ✓			W.R. State Com
Address of Operator			9. Well No.
P.O. Box 1518, Roswell, New Mexico 88201			1
Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER X 660 FEET FROM THE South LINE AND 990 FEET FROM			Alacran Hills Atoka Gas
THE East LINE, SECTION 6 TOWNSHIP 21S RANGE 27E NMPM.			
11. Elevation (Show whether DF, RT, GR, etc.)			12. County
3207' GR - 3222' RKB			Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER Squeeze Perfs., Re-Perf. & Acidize ☒

1. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11,470', PB 11,103'. On 3/31/78, ran tubg. w/RTTS pkr. and loaded hole w/treated water. Spotted 3 sx. sand on ret. bridge plug @ 11,125'. Set pkr. at 10,122' and squeezed perfs. 10,382'-10,390' w/75 sx. Class H cement w/.6 of 1% Halad-9 and 50 sx. Class H cement w/.5 of 1% CFR-2. Max. squeeze press. 6000#. WCC on 4/1/78 & 4/2/78. On 4/3/78, drilled out cement and washed sand off bridge plug. Tagged top of bridge plug at 11,103'. On 4/4/78, perf. 10,608' - 10,620' (Atoka lime) w/2 shots per foot, total of 24 holes. On 4/5/78, acidized perfs 10,608' - 10,620' w/2000 gals. 7½% MSR acid using ball sealers. Max. treating press. 4900#, min. treat. press. 4500#, aver. treat. press. 4500#, aver. inj. rate 3.8 BPM. ISDP 3800#, 5 min. SIP 3550#, 10 min. SIP 3450#. Total load 108 bbls. Swabbed and flowed and recovered all load with slight blow of gas.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John L. Anderson Jr. TITLE Agent DATE 2/20/79

PROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAR 2 1979

CONDITIONS OF APPROVAL, IF ANY: