

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYNMOC COPY
SUBMIT IN TRIPlicate
(Other Instructions on
reverse side)COPY TO
Form Approved
Budget Bureau No. 42 R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 21012

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ JUL 6 19772. NAME OF OPERATOR
Yates Petroleum CorporationD. C. C.
ARTESIA, OFFICE3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 882104. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FSL & 1980' FWL of Section 5-21S-22E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "HQ"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 5-21S-22E
Unit N NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4314' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

PB and Production casing(set)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged back as follows: 8350-8250' w/50 sacks of Class H cement.
Ran 197 joints of 5½" casing as follows: 33 joints of 17# K-55 (1368')
163 joints of 15.5# K-55 (6860'), 1 joint of 17# K-55 (12') (Total 8240')
set at 8240'. 1-Diff-fill collar at 8198'. Cemented w/250 gallons of mud
flush, 280 sacks of Dowell Lite 0.5% CFR-2, 5# kcl, 125 sacks of Class
H 0.5% CFR-2, 5# kcl displaced w/fresh water. PD 10:45 AM 6-2-77.
WOC and tested to 1500#. OK. Ran Temperature Survey and found top
of cement at 7180'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE Geol. Secty

DATE 6-30-77

(This space for Federal or State office use)

APPROVED BY

Joe M. Lala

TITLE ACTING DISTRICT ENGINEER

DATE JUL 5 - 1977

CONDITIONS OF APPROVAL, IF ANY: