

Elevation: 4314 GL = 4329 KB

Spudded: 4-13-77

Atoka Completed 6-17-77

Temp. Aban. 3-20-78

Canyon Completed 4-7-78

15 1/2" hole to 30' GL

13 3/8" 48# K55 Csg set at 30' GL,
cmt'd w/ 3yds ready-mix to surface.

12 1/4" hole to 1100' KB

8 5/8" 24# K55 Csg set at 1100' KB,
cmt'd w/ 775sx c/c, circulated

Top of Glorieta Sh @ 1495' KB

Top of Abn Shale @ 3533' KB

Top of Wolfcamp ls @ 4682' KB

... Top of cement at 5500' (Bond log)

Top of Penn @ 5997' KB

To Commingle - retrieve Bridge Plug from
7523' KB

Top of Canyon @ 6552' KB

Guiberson UNI-VI Pkr w/ On-Off tool
on 2 3/8" Tubing set at 6043' KB

(Wildcat) RISCO PAY

IPF - 549 mcfpd on 4-Pt test

Perf 6020-26 12 0.34" Trd 1000g. 15% DS-30
Perf 6028-32 8 0.34" Trd 800g. 15% DS-30
Perf 6100-10 20 0.34" Trd 1000g. 15% DS-30

Top of Strawn @ 7258' KB

... Retv. Bridge Plug @ 7523' KB on 3-20-78

Top of Atoka @ 7820' KB

(Little Box Canyon) ATOKA PAY

IPF - 445 mcfpd on 4-Pt test

Guiberson UNI-VI Pkr w/ On-Off Tool
@ 7918' KB, w/ Standing Valve.

Perf 7967-78 44 0.32" Trd 2000g. 7 1/2% MSR + N,
Flowed 50" on 1/2" CK

Perf 8076-86 40 0.32" Trd 1000g. 7 1/2% MSR + N,
Flowed 10" on 1/2" CK

Top of Morrow @ 8110' KB

PBTD - 8198' KB

5 1/2" 15.5-17" K-55 Csg set at 8240' KB,
cmt'd w/ 405 sx c/c H & Lite.

7 1/2" TD - 8679' KB