

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

STANDARD FORM NO. 42 R1424
GEOLOGICAL SURVEY

copy to DF
1. If approved, Budget Control No. 42 R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use "APPLICATION FOR PERMIT" for such proposals.)

1. NAME OF OPERATOR
WELL: ☒ GAS ☒ WATER ☒ OTHER

2. NAME OF OPERATOR

Ross, Perry R.

3. ADDRESS OF OPERATOR

Box 2700, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly, and in accordance with U.S. State Regulations)

Box 2700, Midland, Texas 79702

1150' ESL & 1960' FWL of section - Unit located

5. COUNTY OR PARISH

6. ELEVATIONS (Show whether B. S. or O. S.)

OL 3177'

KP 3174.7'

10

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NATURE OF INTENTION TO:

SEQUENCE REPORT OF:

TEST WATER YIELD

PLUG OR ALTER CASING

REPAIR OR PATCH

COMPLETE CONCRETE

TEST OF CASING

MAINTENANCE

REPAIR WELL

REPAIR PLUGS

OTHER:

WATER YIELD

REPAIRING WELL

REPAIRING WELL

ALTERING CASING

TESTING OF CASING

ABANDONING

OTHER: 8 5/8" Intermediate Casing

XXX

See Report results of multiple completion on Well completion or recompletion Report and Log forms.

11. (If the well is to be drilled, completed, or operated, give a detailed description of the work, including estimated date of starting any proposed work. If well is abandoned, include subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 11" hole to 3200'. Ran 75 joints 8 5/8", 32* 5 21# to 3200'. DV tool at 705' and casing packer at 814'. Cemented in two (2) stages: 250 sks Halliburton "light" w/2% CaCl, 1/2 Flowseal and 10# Gilsomite per sack. Tailed in 200 sks Class "C" w/2% CaCl. Pumped plug and set float - held OK. Tested lynes casing packer to 2500*. Dropped plug and opened DV tool. Circulated through tool - circulated 10 sks to pit. Pumped 150 sks Halliburton w/2% CaCl, 1/2 Flowseal and 10# Gilsomite per sk. Tailed with 100 sks Class "C" containing 2% CaCl. Pumped plug and closed DV tool. Tool held OK. Plug down at 7:50 PM, August 29, 1977. Circulated out 30 sks. Tested HOPE to 5000*, tested Hydril to 1500*, pressured DV tool to 3200*. Drilled shoe at 4:00 PM, August 30, 1977.

RECEIVED

SEP 28 1977

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

12. I hereby certify that the foregoing is true and correct

SIGNED

M. J. Haskins

TITLE Senior Production Clerk

DATE Sept. 27, 1977

(This space for Federal or State office use)

APPROVED BY

Lee J. Lane

TITLE

ACTING DISTRICT ENGINEER

DATE

SEP 29 1977

CONDITIONS OF APPROVAL, IF ANY: