

SURFACE INFORMATION

Description (Rate of Flow)	Time	Pressure (P.S.I.G.)	Surface Choke
Opened Tool	0616	-	CLOSED
CLOSED FOR INITIAL SHUT-IN	0619	-	BUBBLE
SURFACE PRESSURE TOO SMALL TO MEASURE			HOSE
FINISHED SHUT-IN	0649	-	"
RE-OPENED TOOL	0650	-	"
GOOD TO STRONG BLOW	0655	2	"
GAS TO SURFACE	0733	3	3/8"
	0800	18	"
	0830	24	"
	0845	36	"
GAS, 160 MCF/DAY	0854	30	"
CLOSED FOR FINAL SHUT-IN	1755	-	"
FINISHED SHUT-IN	1800	-	-
PULLED PACKER LOOSE			

Cushion Type	Amount	Pressure	Bottom Choke
FRESH WATER	2000'	-	Size 5/8"

MUD DATA

Mud Type	DRISPAC-SODASH	Wt.	10.5
Viscosity	32	Water Loss	8.0 C.C.
Resist. of Mud	.07 @ 75	F; of Filtrate	- @ - °F
Chloride Content	163,000		PPM

EQUIPMENT & HOLE DATA

Type Test	M. F. E. OPEN HOLE
Formation Tested	MORROW
Elevation	3177 G.L.
Net Productive Interval	30
Estimated Porosity	6
All Depths Measured From	KELLY BUSHING
Total Depth	11950
Main Hole/Casing Size	7 7/8"
Rot Hole/Liner Size	-
Drill Collar Length	457' I.D. -
Drill Pipe Length	11276' I.D. -
Packer Depth(s)	11764 & 11770

**MULTI-FLOW EVALUATOR
FLUID SAMPLE DATA**

Sampler Pressure	75	P.S.I.G. at Surface
Recovery: Cu. Ft. Gas	.33	
cc. Oil	-	
cc. Water	-	
cc. Mud	-	
Tot. Liquid cc.	-	
Gravity	-	°API @ - °F.
Gas/Oil Ratio	-	cu. ft./bbl.

RESISTIVITY**CHLORIDE CONTENT**

Recovery Water	- @ - °F.	- ppm
Recovery Mud	- @ - °F.	- ppm
Recovery Mud Filtrate	- @ - °F.	- ppm
Mud Pit Sample	.07 @ 75 °F.	163000 ppm
Mud Pit Sample Filtrate	- @ - °F.	- ppm

RECOVERY DESCRIPTION	FEET	BARRELS	% OIL	% WATER	% OTHERS	API GRAVITY	RESISTIVITY	CHL. PPM
FRESH WATER CUSHION	2000	-				@ °F.	1.45 @ 75 °F.	500
DRILLING FLUID	352	-				@ °F.	.48 @ 75 °F.	3460
						@ °F.	@ °F.	
						@ °F.	@ °F.	
						@ °F.	@ °F.	
						@ °F.	@ °F.	
						@ °F.	@ °F.	

Remarks: _____

Address: P. O. BOX 2760; MIDLAND, TEXAS 79701

Company: BASS ENTERPRISES PRODUCTION COMPANY
 Well: BIG EDDY UNIT #54

Test Interval: 11770' TO 11950'

Location: 1180' FSL & 1980' FWL-SEC.29-T21S-R28E
 Test #: 1

Field: BIG EDDY
 Date: 9-29-77

County: EDDY

State:

NEW MEXICO

Technician: VANDVENTER (HOBBS)

Test Approved By:

MR. D. L. SCHILLING

Field Report No. 05811 D
 No. Reports Requested 7