

UNMOCC COPY.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 6005

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brainerd Fed. "10"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1-22S-21E

Unit B

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210 C.E.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FEL of Sec. 1-22S-21E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

4599' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Prod csg & PB

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9089' - Verbal approval was given by Mr. Jo Lara, Acting District Engineer, USGS in Artesia, NM to plug back well as follows: 8050-7900' 50 sacks of Class H cement; 7550-7400' 50 sacks Class H cement; 6650-6500' 50 sacks of Class H cement (Cisco formation).
Ran 155 joints of 4½" 10.5# J-55 (6483') of casing, 1-Guide shoe at 6483', Diff-Fill Collar at 6441'. 8 centralizers. Cemented as follows: 250 gallons mud flush, 400 sacks of Howco Lite 6/10% CFR-2 + 5#/sack kcl. 150 sacks Class C 6/10% CFR-2 + 5#/sack kcl. PD 11:40 AM 12-19-77. Set slips and tested to 1500#. OK. WOC and ran Temperature Survey found top of cement at 3520'. WLPBTD 6426'.

RECEIVED
JAN 18 1978
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine J. Johnson

TITLE

Geol. Secty

DATE 1-17-78

(This space for Federal or State office use)

APPROVED BY

Jo Lara

TITLE

ACTING-DISTRICT ENGINEER

DATE

JAN 18 1978

CONDITIONS OF APPROVAL, IF ANY: