

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on reverse side)

NMOCC COPY

Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM - 25493

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 7

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indian Basin (Morrow)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

7, T-21-S, R-24-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

COTTON PETROLEUM CORPORATION

AUG 23 1977

3. ADDRESS OF OPERATOR

420 Wall Towers West, Midland, Texas, 79701 O.C.C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State law.
See also space 17 below.)
At surface

1650' FN & EL, Sec. 7, 21-S, 24-E, Eddy County, NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3813 GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.)*

8/4/77 Potential Morrow, Atoka, Strawn production zones tested water and captioned well was permanently plugged by Halliburton this date. 350' 13 3/8" 48# H-40 and 3270' 8 5/8" 32# K-55 with cement circulated to surface was left in the hole. The hole was loaded with 9.5#/gal. mud with viscosity of 41 and the following plugs were spotted:

75 sx Class C Neat cement 9350 - 9500
75 sx Class C Neat cement 8150 - 8300
75 sx Class C Neat cement 6850 - 7000
50 sx Class C Neat cement 4800 - 5000
50 sx Class C Neat cement 3220 - 3320
20' plug and steel marker at surface.

RECEIVED
AUG 19 1977
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

You will be advised when location is ready for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Division Production Mgr.

DATE 8-17-77

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE AUG 22 1977

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.