

**UNITED STATES DEPARTMENT OF THE INTERIOR**  
**GEOLOGICAL SURVEY**

**NMOCC COPY**

SUBMIT IN TRIPLI  
(Other instructions  
verse side)

E\*  
re-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 13968

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Huber "IA" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 15-21S-21E  
Unit G NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.  
At surface

1880' FNL & 1980' FEL of Sec. 15-21S-21E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4672' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

TD 1340' - Ran 31 joints of 8-5/8" 24# K-55 casing (1326') set at 1324'.  
1-Guide shoe, 2 centralizers and 2 cement baskets at 1017 and 725'.  
Cemented w/150 sacks of Thick-set w/2% CaCl followed w/500 sacks of  
Howco-Lite w/10# gilsonate per sack, 1/4# flocele/sack 2% CaCl followed  
w/150 sacks of Class C 2% CaCl. Cement did not circulate. PD 9:00 AM  
12-13-77. WOC 6 hours and Ran Temperature Survey, found top of cement  
at 620'. Ran 1" to 500' unable to circulate hole w/1". Filled hole  
w/8 1/2 yards of Ready-mix to surface. WOC 18 hours, cut off casing, nipped  
up and tested BOP's to 1600#. OK. Reduced hole to 7-7/8", drilled plug and  
tested to 600#. OK. Resumed drilling.

RECEIVED

JAN 4 1978

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Geol. Secty

DATE

1-4-78

(Leave blank for District Engineer's use)

APPROVED BY

ACTING DISTRICT ENGINEER

DATE

JAN 6 - 1978

CONDITIONS OF APPROVAL, IF ANY: