

NMCCC COPY

Form 10-74
May 1974UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42 R1421

LEASE DESIGNATION AND SERIAL NO.

LM 13968

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

1880' FNL & 1980' FEL of Sec. 15-21S-21E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4672' GR

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 15-21S-21E

Unit G NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set Prod. Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD Drillers 8125; LTD 8048'. Verbal approval was given by Mr. Jim Knauf, USGS Supervisor, Artesia, NM to plug back well as follows: 7750-7600' 50 sacks of Class H cement. 7250-7100' 50 sacks of Class H cement, 6200-6070' 50 sacks Class H cement, 4820-4675' 50 sacks Class H cement. Job completed 3:17 PM 1-19-78. Ran 112 joints of 4½" 10.5# K-55 (4671') of casing set at 4671'. 1-Guide shoe at 4671'. Diff-Fill collar at 4669'. 5-centralizers. Cemented as follows: w/250 gallons of mud flush, 290 sacks of Howco-Lite + 5/10% CFR-2 + 4#/sack KCL tailed in w/350 sacks of Class C 4/10% CFR-2 5#/sack KCL displaced w/2% KCL water. PD 12:30 AM 1-20-78. WOC and ran Temperature Survey found top of cement at 1840'. Tested to 1500#. OK.

RECEIVED

MAR 21 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

APPROVED *Christine Anderson*

TITLE Geol. Secty

DATE 3-17-78

(This space for Federal or State use)

APPROVED BY *J. J. Lara*

TITLE ACTING DISTRICT ENGINEER

DATE APR 4 - 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side