

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 13968

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Huber "IA" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat (Box Canyon Area)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit G

Section 15-21S-21E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4672' GR; 4682' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.) *

We now propose to plug and abandon this well. 4½" casing is set at 4671' KB and perforated at 4616-24', 4250-4373', 3859-4065'; 3390-3506'; 2305-13'; 2127-39'. We propose to displace hole with mud, spot cement plugs across perforations, cut off and pull 4½" casing at about 1800', spot cement plugs as follows:

4400-3800	40 sacks Class "C"
3560-3330	15 sacks Class "C"
2330-2100	15 sacks Class "C"
1820-1700	35 sacks Class "C"
20-surface	5 sacks Class "C"

Will install dry hole marker and prepare location for inspection.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 11-13-78

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE DEC - 5 1978

CONDITIONS OF APPROVAL, IF ANY:

Subject to setting a 100ft. plug across
the shoe of the 8½" casing.

*See Instructions on Reverse Side