

COPIES RECEIVED	3
TRIBUTION	
FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SEP 14 1977

**D. O. C.**  
ALBUQUERQUE, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-5058	

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name
2. Name of Operator Penroc Oil Corporation ✓		8. Farm or Lease Name Allied "A" Comm.
3. Address of Operator P. O. Drawer 831, Midland, Texas 79702		9. Well No. 2
4. Location of Well UNIT LETTER O, 1700 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 22 TOWNSHIP 20 S RANGE 27 E NMPM.		10. Field and Pool, or Wildcat Penton Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 3271' GR		12. County Eddy

16.

**Check Appropriate Box To Indicate Nature of Notice, Report or Other Data**

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/19/77: Well spudded @ 2:00 pm 8/19/77.

8/22/77: Ran 32 jts 9 5/8", 47#, N-80, LT&C casing being set @ 1296'. Cemented w/200 sxs thickset, 1/2# Flo-seal, 12# Gilsonite, 2% CaCl followed w/175 sxs Halliburton Lite, 10# Gilsonite, 1/4# Flo-seal, 2% CaCl, followed w/200 sxs Class C, 2% CaCl. Plug down 12:15 pm 8/22/77. No circulation. Top of cement by temp. svy. 764'. Go in w/1" tbg, pump down 50 sxs Class C cement, brought level to 712'. Pump down 50 sxs Class C cement, brought level to 692'. Pump down 50 sxs Class C cement, brought level to 632'. Pump down 250 sxs Class C cement and circulated. WOC 18 hrs. Pressured to 1000# for 40 mins. Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. J. Dickey TITLE President DATE 9/12/77

APPROVED BY W. A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE SEP 15 1977

CONDITIONS OF APPROVAL, IF ANY: