

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
reverse side)

Copy to SE
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM 13968	
2. NAME OF OPERATOR Yates Petroleum Corporation ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 207 South 4th Street- Artesia, NM 88210		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1270' FEL of Sec. 15-21S-21E		8. FARM OR LEASE NAME Huber "IA" Federal	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4549' GR		10. FIELD AND POOL, OR WILDCAT Undesignated	
		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA Sec. 15-21S-21E Unit P NMPM	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8050' - Ran 184 joints of 5½" 15.5# K-55 (7717') of casing. 1-Guide shoe at 7717', Diff-Fill Collar at 7675'. 7-centralizers. Cemented as follows: 430 sacks of Howco Lite + 5/10% CFR-2 + 5#/sx KCL + 5#/sk gilsonite and tailed in w/200 sacks of Class C + 5.10% CFR-2 + 5#/sx KCL. PD 2:30 PM 9-5-77. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 4800'. WLPBTD 7653'. Drilled out cement and cleaned out hole to 7891' and ran liner as follows: Ran 247' of 3½" 9.3# Hydril A-95 liner inside 5½" casing. Cemented w/55 sacks of Class H 5/10% CFR-2 and 5# KCL set at 7891'. Top of liner at 7644'. WOC. and tested to 1000#. OK.

RECEIVED

JAN 24 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 1-23-78.

(This space for Federal or State office use)

APPROVED BY Joe S. Lara TITLE ACTING DISTRICT ENGINEER DATE JAN 25 1978
CONDITIONS OF APPROVAL, IF ANY: