

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 067144

6. INDIAN ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

OIL ☒ GAS ☐ OTHER ☐
WELL ☒ WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

Box 2760, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State **ARTESIA OFFICE**
See also space 17 below)
At surface

2310' FSL & 1650' FWL of section - Unit letter K.

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, TO, OR, etc.)

3171.5' GL 3184.5' KB

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

58

10. FIELD AND POOL, OR WILDCAT

Indian Flats Delaware

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35, T21S, R28E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETION ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) ☐Spud date & surface casing ☒Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded January 19, 1978. Drilled 12 1/4" hole to 398'. Ran 8 5/8" casing and set at 398' with 300 sks cement. (200 sks containing 4% gel, 2% CaCl₂ and 1/2# Flocele per sack - tailed with 100 sks Class "C" containing 2% CaCl₂). Plug down at 5:30 AM, 1-21-78. Bumped plug with 500 psi. Pressure tested BOPE & 8 5/8" casing to 950 psi for 30 Min. Held OK. Drilled out with 7 7/8" bit.

RECEIVED
FEB 24 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Marty, Jr.

TITLE

Senior Production Clerk

DATE

Feb. 23, 1978

(This space for Federal or State office use)

APPROVED BY

Lee J. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

FEB 27 1978

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.