

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

PERRY R. BASS

3. ADDRESS OF OPERATOR

BOX 2760, MIDLAND, TX 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FSL & 1650' FWL - UNIT K

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON ☐

(other) ADD PERFORATIONS

SUBSEQUENT REPORT OF:

☐

☒

☒

☐

☐

☐

☐

☐

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/8/84: PULLED RODS & TUBING. RAN CASING GUN LOADED W/10 558-II CHARGES. PERFORATED '49ER' DELAWARE W/10 SHOTS (1 SHOT @ EACH DEPTH - 3666', 3667', 3669', 3671', 3680', 3682', 3684', 3686', 3688' & 3690'). RAN TUBING - TAGGED PBD @ 3729'. SET BPC @ 3727' & PKR @ 3587'.

3/9/84: ACIDIZED PERFS 3666'-3690' W/1000 GALS HCl (15%).

3/10/84: SWABBING - 50-50 OIL & WATER.

3/11/84: SWABBING - 50-50 OIL & WATER. PREPARING TO FRAC PERFS 3666'-3690'.

3/12/84: SWABBED & ATTEMPTED TO FRAC.

3/13/84: FRAC'D PERFS 3666'-3690' W/15,000 GALS FOAM & 25,760 # 20/40 SAND. FLOWED BACK AN ESTIMATED 15 BBL'S OIL & 50 BBL'S WATER.

Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. B. Murty, Jr. TITLE Asst. Dir. DATE March 22, 1984

ACCEPTED FOR RECORD (Leave space for Federal or State office use)

APPROVED BY SWB CONDITIONS OF APPROVAL, IF ANY

TITLE DATE

MAY 16 1984

NEW MEXICO *See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

3/14/84: SWABBED 37.5' BBLs OIL + 125' BBLs WATER. PREPARING TO FRAC PERFS 3544' - 3553'.

3/15/84: RETRIEVED BP - PULLED UP + SET BP @ 3606'. SET PKL @ 3447' - TESTED TO 1000' -

HELD OK. SWABBED.

3/16/84: FRAC'D PERFS 3544' - 3553' W/ 9500 GALS FOAM + 13,500# 20/40 SAND.

13/17/84: SWABBED - REC 25 BBLs OIL + 41 BBLs WATER. PREP TO PUT ON PUMP.

13/18/84: SD - SUNDAY.

3/19/84: KILLED WELL. RAN TBG - SN @ 3690' + ANCHOR @ 3430'. RAN PUMP + RODS - PUT WELL TO PUMPING @ 5:00 PM. PRODUCING FROM BOTH SETS OF PERFS.

3/20/84: 8 HR TEST; (P) 0 OIL + 33 BBLs WATER.

3/21/84: 24 HR TEST; (P) 11 BBLs OIL + 132 BBLs WATER. ON ROUTINE PRODUCTION.