

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)copy to SF
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM-25494	
2. NAME OF OPERATOR DEPCO, Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 800 Central, Odessa, Texas 79761		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit Letter 3 1980 PS & EL, 6-21-24		8. FARM OR LEASE NAME Shell Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3778.8 GR		10. FIELD AND POOL, OR WILDCAT Und. Cemetery Morrow Gas	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 6-21-24	
		12. COUNTY OR PARISH Eddy	
		13. STATE N. Mex.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Commencement

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-23-77 Spudded 9:00 AM.

8-25-77 Drilled 17 1/2" hole to 453'. Set 13 3/8" H-40 48# csg. at 447'. Cemented w/300 sx. Lodense, 1/4" Celco Flakes & 5# Gilsontite per sx. Followed w/200 sx. Class "C" w/2% ca. cl. Cement circulated. WOC 18 hrs. Tested csg. at 1000# for 30 min. Held OK.

8-31-77 Drilled 11" hole To 2454'. Set 4 jts. (165') 8 5/8" 32# J-55, 49 jts. (1974') 8 5/8" 24#, 8 jts. (315) 32# J-55 csg. set at 2454'. Cemented w/900 sx. Lodense, 1/4" Celco Flakes, 10# Gilsontite & 2% ca. cl. Followed w/200 sx. Class "C" w/2% ca. cl. Cement circulated. WOC 18 hrs. Tested pipe cement & BOP at 1000# 30 minutes. Lost 15# in 30 minutes.

RECEIVED

OCT 11 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED D. R. MasonTITLE Chief ClerkDATE 10-7-77

(This space for Federal or State office use)

APPROVED BY Lee J. Lora
CONDITIONS OF APPROVAL, IF ANY:TITLE ACTING DISTRICT ENGINEERDATE OCT 17 1977

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.