

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Yates Petr. Corp.</i>		Lease <i>Stonewall EP state</i>		Well # <i>3</i>	
Location of Well	Unit <i>5455 1960 W</i>	Section <i>19</i>	Township <i>20</i>	Range <i>28</i>	County <i>Eddy</i>
Drilling Contractor <i>Byrd Drilling Co.</i>			Type of Equipment <i>Rotary to start 8-2-77</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen.
<i>17 1/2</i>	<i>13 3/8</i>	<i>61</i>		<i>550</i>	<i>350 circ.</i>
* <i>12 1/4 or 11"</i>	<i>8 3/8</i>	<i>24</i>		<i>2900</i>	<i>1000 circ.</i>
<i>7 7/8</i>	<i>5 1/2</i>	<i>15.5</i>		<i>4800</i>	<i>200</i>

Casing Data:

*12 3/4 - 32#
53 3/4 - 24#*

Surface *65* joints of *8 5/8* inch *24 1/2* # Grade *J-55*

✓

(Approved) (Rejected)

Inspected by *mu*

date *8/11/77*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required *1450*

Type of Shoe used *Guide* Float collar used *Insert* Btm 3 jts welded *Yes*

TD of hole *7372* Set *7272* Feet of *8 5/8* Inch *24 1/2* # Grade *J-55*

New-used csg. @ *7372* with *0* sacks neat cement around shoe

+ *200* sax Reg Flow/12% *53* additives + *1100* *52* *40* *1/2* *1/4* *1/8* *1/16*

Plug down @ *10:30* (AM) (PM) Date *8/15/77*

Cement circulated *No* No. of Sacks

Cemented by *Dowell* Witnessed by *mu*

Temp. Survey ran @ *4:30* (AM) (PM) Date *8/15/77* top cement @ *55-520*

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Centrifuges @ 700-850-2860 Barbed @ 750-550*

Cement locked up w/ cement @ 1875' inside 8 5/8" (All of Neat Cement)

C 2700#

8/16/77 Ran 1" to 565' - Pumped 190 sx class C w/20% CC