

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYEASE  
Form 25347

C/SF

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR Monaco Oil Co.  
Gas Lift Sales & Service, Inc.3. ADDRESS OF OPERATOR  
2209 West Industrial Avenue Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1880' FNL &amp; 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☒REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☒ABANDON\* ☐

(other)

6. IF INDIAN, ALLOTTEE OR **RECEIVED**7. UNIT AGREEMENT NAME  
**JUN 23 1983**8. FARM OR LEASE NAME  
Catclaw Federal **O. C. D.**9. WELL NO. **ARTESIA, OFFICE**  
**1**10. FIELD OR WILDCAT NAME  
Revelation11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
sec. 10 T-22-S, R-25-E12. COUNTY OR PARISH **Eddy** 13. STATE  
**New Mexico**

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
RKB 3609**RECEIVED**  
(NOTE: Report results of multiple completion or zone change on Form 9-330.)**MAY 17 1983**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set CIBP at 10,000' with ~~10~~ cement on top. Perforate Canyon @ 9056-9076, stimulate with 4000 gallons 7-1/2% acid + N2. Swab well back and put on production. If Canyon not productive, set CIBP @ 9000' with ~~10~~ cement on top. Perforate Cisco at 8858'-8866' and 8872'-8880'. Stimulate with 4000 gallons 7-1/2% acid + N2. Swab well back and put on production. Work will start approximately June 15, 1983.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Edt. Channing TITLE President DATE 05-16-83APPROVED BY Peter W. Chester TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

**JUN 22 1983**

\*See Instructions on Reverse Side

Post FD-2  
9-16-83  
P.H. Hoot Z...