

COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 3047

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Texas Hill KM ~~Ed.~~

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat *inc.*11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 21-21S-21E

Unit H NMMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER

RE-ENTRY

APR 25 1979

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

O.C.C.

3. ADDRESS OF OPERATOR

207 South 4th Street- Artesia, NM 88210

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1836'' FNL and 915' FEL of Sec. 21-21S-21E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4651'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Set Prod csg & Spud ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was drilled to a total depth of 6200' and P&A by Mallard Exploration Inc. as their Federal #1 "21". Yates re-entered the hole at 11:00 PM 3-16-79. Will clean out to approx. 8400'.

TD 7835' - Ran 253 joints of 4½" K-55 11.6# & 10.5# ST&C casing as follows: 26 joints 11.6# (1045') and 178 joints 10.5# (6797') (Total 7842' of casing set at 7836'. 1-Guide shoe at 7836'. Diff-Fill Collar at 7834'. 15-centralizers. Dropped wrong size ball to activate Diff-Fill Collar - plugging collar. Perforated casing to cement w/5½" holes at 7834-7833'. Set cement retainer at 7793'. Cemented w/250 gallons mud flush, 400 sacks Howco-Lite 6/10% CFR-2, 2/10% Halad-22, 5#/sack KCL followed w/150 sacks of Class H 6/10% CFR-2, 2/10% Halad-22, 5#/sack KCL. PD 5:20 PM 4-8-79. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 5550'. WLPBTD 7760'.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Johnson*

TITLE

Geol. Secty

DATE

4-21-79

(This space for Federal or State office use)

APPROVED BY

(Orig. Sgd.) ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

DATE

APR 24 1979

CONDITIONS OF APPROVAL, IF ANY: