

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
**Nearburg Producing Company**

3. Address and Telephone No.  
**3300 North A Street, Building 2, Suite 120, Midland, Texas 79705 (915) 686-8235**

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
**1,924' FNL and 1,647' FEL, Section 12, T21S, R21E**

5. Lease Designation and Serial No.  
**NM - 94577**

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.  
**Little Box Canyon 12 Federal #1**

9. API Well No.  
**30-015-12288**

10. Field and Pool, or Exploratory Area  
**Little Box Canyon - Morrow**

11. County or Parish, State **80240**  
**Eddy County, New Mexico**

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other Plug and Abandonment
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1.) Set 45 sx cement plug from 5,975' - 5,825'.
- 2.) Set 30 sx cement plug from 4,880' - 4,980'.
- 3.) Set 30 sx cement plug from 3,500' - 3,400'.
- 4.) Set 30 sx cement plug from 1,850' - 1,750'.
- 5.) Set 30 sx cement plug from 350' - 250'.
- 6.) Set 30 sx cement plug from 50' - surface.
- 7.) ND BOPE. Cut off casing and cap well.
- 8.) Clean pits and release rig at 2401 hrs 9/23/98.
- 9.) P&A'd well. Final Report.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed David R. Glass  
(This space for Federal or State office use)

Title **Manager of Drilling and Production**

Date **9/30/98**

Approved by **(ORIG. SGD.) DAVID R. GLASS**  
Conditions of approval, if any:

Title **PETROLEUM ENGINEER**

Date **OCT 20 1998**

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

92222-77-42

RECEIVED

OCT 5 '98

BLM  
ROSWELL, NM