

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

O.C.C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	L-5129

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Hanagan Petroleum Corporation ✓ 3. Address of Operator P.O. Box 1737, Roswell, New Mexico 88201 4. Location of Well UNIT LETTER J, 1980' FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 30 TOWNSHIP 20S RANGE 27E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3227 GL - 3243 KB	7. Unit Agreement Name 8. Farm or Lease Name Mandy 9. Well No. 1 10. Field and Pool, or Wildcat Avalon Morrow 12. County Eddy
--	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER Plug back & running casing <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

11/15/77: Permission from Mr. Mermis w/N.M.O.C.C. to plug back well
11/16/77: T.D. 10680' plug in this manner w/Howco cementing w/all Class "C" cement & all 35 sx plugs @ 10,300 to 10,400' - 9775' to 9875' - 9300' to 9400' - 8375' to 8475' - 7775' to 7875' - 6100' to 6200' - 5450' to 5550' - 3125' to 3225 - Mud between all plugs.
11/17/77: P.B. T.D. 3125' ran 80 jts. 4½" 9.5# Lt & C and ST&C J55 casing set @ 2734', cemented w/350 sx Class "C" w/50-50 Poz - 5# salt per sx - 4/10 of 1% of CFR-2 plug down @ 2:45 A.M. 11/17/77, temp. survey top cement @ 1750'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>ML. Southerland</u>	TITLE <u>Agent</u>	DATE <u>11/29/77</u>
APPROVED BY <u>W.A. Gussert</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>DEC 1 1977</u>
CONDITIONS OF APPROVAL, IF ANY:		