Form 9-331 (May 1963)	DEPARTMENT OF THE INTERIO	SUBMIT IN TI ICATE (Other Instructions on r Verse side)	5. LEASE DESIGNATION AND BERIAL NO. NM-25351	
	NDRY NOTICES AND REPORTS C is form for proposals to drill or to deepen or plug be Use "APPLICATION FOR PERMIT" for such pro		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
			7. UNIT AGREEMENT NAME	
WELL WELL 2. NAME OF OPERATOR	X OTHER Dry Hole		S. FARM OR LEASE NAME	
Rial Oil C	ompany /	1001	Rock Tank Federal	
ADDRESS OF OPERAT	V	- <u>pri pri ca</u>	0, WELL NO.	
P. O. Draw	er 3068, Midland, Texas 79702	CRYECA, OFNCE	1	
. LOCATION OF WELL See also space 17 b At surface		10. FIELD AND POOL, OR WILDCAT		
	1315' FSL & 2080' FWL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T-22-S, R-25-H	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, 3991' GR	RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE Eddy N.M.	
6.	Check Appropriate Box To Indicate No	ature of Notice, Report, or	Other Data	
	NOTICE OF INTENTION TO:		QUENT REPORT OF :	
		-		
TEST WATER SHUT		WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT Shoot or acidize	MULTIPLE COMPLETE	FRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERING CASING ABANDON MENT* X	
REPAIR WELL	CHANGE PLANS	(Other)		
(Other)		(NOTE : Report resul	ts of multiple completion on Well pletion Report and Log form.)	
	Plug #1 set @ 10,600 - 10,300, c Plug #2 set @ 9,700 - 9,400, cer Plug #3 set @ 8,350 - 8,200, cer Plug #4 set @ 7,500 - 7,350, cer Plug #5 set @ 4,000 - 3,900, cer Plug #6 set @ 2,500 - 2,400, cer Top of 8-5/8" casing - cemented	mented with 90 sacks mented with 45 sacks mented with 45 sacks mented with 30 sacks mented with 20 sacks	S Class C, S Class C, S Class C, S Class C, S Class C, S Class C,	
	4" marker installed at top of we	ell showing all pert	RECEIVED	
			JUN 4 1980	
			U.S. GEOLOGICAL SURVEY ARTESIA, NEW MEXICO	
18. I hereby certify th	at the foregoing is true and correct			
SIGNED	deral or State office use)	Camptroller		
Orig	Set.) PETER W. CHESTER TITLE		DATE	
-	FOR			
	JAMES A. GILLHAMSee Instructions DISTRICT SUPERVISOR	on Reverse Side		