

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1993, Roswell, NM 88202 1-505-623-6699

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UNIT LETTER H, 1980' FNL & 990 FEL
SEC. 30, T-20S, R-29E

5. Lease Designation and Serial No.

NM-03677

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

STEBBINS DEEP FED. # 1

9. API Well No.

30-015-10794

10. Field and Pool, or Exploratory Area

SCANLAN DELAWARE

11. County or Parish, State

EDDY CO., NM.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other P&A

- ☐ Change in Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

P&A PROCEDURE

PBTD = 10,373'

OPEN PERFS: 3238-40' & 3339-41.5' (DELAWARE)

CALL BLM 24 HOURS PRIOR TO PLUGGING

- 150' PLUG (TOP OF WOLFCAMP) 9190-9040'
- 100' PLUG (TOP OF BONE SPRING) 5790-5690'
- 350' PLUG +/- FROM 3400-3070' (ACROSS DELAWARE PERFS & INTERM. SHOE. @ 3170').
- 100' PLUG FROM 770' TO 670' (SURFACE SHOE)
- 50' SURFACE PLUG & DRYHOLE MARKER.

NOTE: 350' PLUG TO COVER PERFS, INTERM. SHOE & INTER. OF BAD PIPE IDENTIFIED ON 10-13-94 AS BAD PIPE DURING TEST.

ABOVE APPROVED BY SHANNON SHAW-BLM 1-6-95 rfn

BACKFILL PITS, CLEAN LOCATION &
PREPARE TO REHAB LOCATION

14. I hereby certify that the foregoing is true and correct

Signed

Ray F. Nokes

RAY F. NOKES

Title

PROD. MGR./ ENG.

Date 1/6/95

(This space for Federal or State office use)

Approved by (ORIG. SGD.) JOE G. LARA

Title

PETROLEUM ENGINEER

Date

2/9/95

Conditions of approval, if any:

See attached. Also tag plug @ step #3.