

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 9187

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAR - 7 1978

7. UNIT AGREEMENT NAME

O. C. C.
ARTESIA OFFICE

8. FARM OR LEASE NAME

Box Canyon "4A"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 23-21S-21E
Unit B NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 1980' FEL of Sec. 23-21S-21E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4592' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☒

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Set Prod. csg & PB

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8400' - Verbal approval was given by USGS in Artesia, NM to plug back well as follows: 8000-7850' w/50 sacks of Class H cement. 6650-6500' w/50 sacks of Class H cement. WOC. Ran 150 joints of 5½" 15.5# K-55 (6515') of casing set at 6486'. 1-Guide shoe at 6486', 1-Diff-Fillcollar at 6486'. 10 centralizers at 6450, 6410, 6370, 6300, 6100, 6030, 5990, 5940, 5910, 5870. Cemented w/250 gallons of mud flush, 10 bbls KCL water 380 sacks of Howco-Lite, 5#/sx gilsonite, 200 sx Class C 5/10% CFR-2 + 5#/sx KCL displaced w/40 bbls KCL water. PD 10:15 PM 2-6-78. WOC. Ran Temperature Survey and found top of cement at 4300'.

RECEIVED
MAR 1 - 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE Geol. Secty

DATE 2-28-78

(This space for Federal or State office use)

APPROVED BY

Joe L. Lala

TITLE ACTING DISTRICT ENGINEER

DATE MAR 6 - 1978

CONDITIONS OF APPROVAL, IF ANY: