

OCC COPY

Copy to 2.1.

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM - 0559177

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FWL, Sec 8, T-21-S, R-25-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3415'

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nopal Draw Federal Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 8, T-21-S, R-25-E

12. COUNTY OR PARISH

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 7 7/8" hole at 10,365' at 4:15 PM 2-8-78. Ran 269 jts and 1 cut jt 5 1/2" 17# and 15.50# K-55 & N-80 LT & C casing 10,351.40' set at 10,365'. (5392' 15.50# K-55) (3822' 17# K-55) (1135' 17# N-80). Cemented with 900 sacks Class H w/ .75% CFR-2 and 4#/sack KCL, plug down at 3:30 AM 2-11-78. WOC 6 hrs. TSITOC 6800'. WOC over 24 hours. Piped valves out of cellar on all casing strings, approved by Bill Grisset OCC Artesia, NM. *Checked Marked Valves in 1/20/77.*

OK M.S.

Tested 5 1/2" casing to 3000# for 30 min - OK.

RECEIVED
MAR 2 - 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

NOTE: This information considered CONFIDENTIAL.

18. I hereby certify that the foregoing is true and correct

SIGNED *N. P. Liles, Jr.*

TITLE Area Engineer

DATE 2-28-78

(This space for Federal or State office use)

APPROVED BY *Joe L. Lara*

TITLE ACTING DISTRICT ENGINEER

DATE MAR 3 - 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side