Copy To JTS

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [XX] GAS WELL [ ] OTHER

5. LEASE DESIGNATION AND SERIAL NO.: LC 067144

6. IF INDIAN, ALLOTTEE OR TRIBE NAME: ---

7. UNIT AGREEMENT NAME: Big Eddy Unit

2. NAME OF OPERATOR: Perry R. Bass

RECEIVED

8. FARM OR LEASE NAME: Big Eddy Unit

3. ADDRESS OF OPERATOR: Box 2760, Midland, Texas 79702

APR 17 1978

9. WELL NO.: 59

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface

O. C. C. ARTESIA, OFFICE

10. FIELD AND POOL, OR WILDCAT: Indian Flats Delaware

1650' FWL & 990' FNL of section - Unit letter C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 35, T21S, R28E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 3183' GL 3197' KB

12. COUNTY OR PARISH: Eddy

13. STATE: New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]	(Other) Spud date & 8 5/8" csg stg			[XX]
(Other)			[ ]	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded 12¼" hole @ 4:45 PM, April 3, 1978. Drilled to 410' - ran 10 jts 8 5/8" 24#, K-55, ST&C casing - set @ 410'. Cemented w/200 sks Class "C" + 4% gel, + 2% $CaCl_2$. Tailed w/100 sks Class "C" + 2% $CaCl_2$. Circulated 33 sks to pit. Bumped plug to 750#. Installed casing head - tested blind rams to 750# - held OK - tested pipe rams to 1000# - held OK. Drilled cement & shoe after WOC time of 31 3/4 hours.

RECEIVED
APR 12 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED W. R. Wurtz, Jr. TITLE Senior Production Clerk DATE April 10, 1978

(This space for Federal or State office use)

APPROVED BY Joe D. Lara TITLE ACTING DISTRICT ENGINEER DATE APR 14 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-379