

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NMOCC COPY

SUBMIT IN TRIPT
(Other instruction:
verse side)

TE
re

copy to SF

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Superior Federal
NM-0144698

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

No

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Superior Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

East Burton Flat (Morrow)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 5, T20S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ RECEIVED

2. NAME OF OPERATOR

The Petroleum Corporation

3. ADDRESS OF OPERATOR

3303 Lee Parkway, Dallas, Texas 75219

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

ARTESIA, OFFICE

Unit I, 1980' FSL and 660' FEL

14. PERMIT NO.

None assigned

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 3292.2

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

This well was spudded 12 noon 1/18/78.

Drilled 17-1/2" hole to 402 feet. Ran 408 feet of 13-3/8" 48# H-40 ST&C new casing and cemented with 480 sacks Class C cement with 2% CaCl. Circulated approximately 45 sacks cement. Waited on cement 21 hours. Cut off 13-3/8" casing. Welded on Rector 13-3/8" x 12"-3000psi landing base and tested to 1000 psi. Nipped up blowout preventers and tested casing to 1000 psi.

RECEIVED
JAN 25 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Don F. Tankersley

TITLE Vice President of Operations DATE 1/23/78

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE JAN 26 1978

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side