NO. OF COPIES RECEIVED		Form C-103			
DISTRIBUTION		Supersedes Old SRM 1216 C-102 and C-103			
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65			
FILE	MAR 2 0 1978	API 30-015-22398 5			
U.S.G.S.	5a. Indicate Type of Lease				
LAND OFFICE		State Fee XX			
OPERATOR	5. State Oil & Gas Lease No.				
· · · · · · · · · · · · · · · · · · ·	ARTESIA, DEFICE				
SUND (DO NOT USE THIS FORM FOR PU USE "APPLICA	RY NOTICES AND REPORTS ON WELLS ROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. STION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)				
±.		7. Unit Agreement Name			
WELL GAS WELL	OTHER.	Big Eddy Unit			
2. Name of Operator	8. Farm or Lease Name				
Parry R. Inso	Big Eddy Unit				
5. Adarous of Operator		9. Well No.			
Dem 2760, Midland, T	60				
4. Location of Well	10. Field and Pool, or Wildcat				
UNIT LETTER	Undos. Bass Morrow				
THE EAST LINE, SECT	10N 20 TOWNSH P 215 RANGE 28E NMPM.	ΛΙΙΙΙΙΙΙΙΙΙΙΙΙΙ			
	15. Elevation (Show whether DF, RT, GR, etc.)				
	12. County				
	3204.3' GL 3222.3' KB	Eddy			
10. Check	Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data			
	INTENTION TO: SUBSEQUENT				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	ALTERING CASING			
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT			
PULL OR ALTER CASING	CHANGE PLANS \Box casing test and cement JQB X				
	OTHER	[_]			
OTHER					
	Departions (Clearly state all pertinent details, and give pertinent dates, including	antimated data of station and process			
work) SEE RULE 1103.	sporations (around) arous and portanent actions, and give personent autoat inclauting	termine and of training any proposed			

Drillod 11" hole to 3200'. Ran calipar log. Ran 8 5/8" 24 & 32#, K-55 casing. DV tool at 800'. Set casing at 3199.00'. Commented 1st stage w/475 sks Hallco "Lite" with 2% CaCl2 plue ½% Flocele per sack. Tailed with 200 sks Class "C" w/2% CaCl2. Plug down at 2:00 FM, February 5, 1978. Circulated 90 sks through DV tool. Cemented 2nd stage w/ 150 sks Hallco "Lite" w/2% CaCl2 & ½% Flocele per sk. Tailed with 100 sks Class "C" w/ 2% CaCl2. Plug down at 6:30 PM, February 5, 1978. Circulated out 50 sks. Tested DV tool and shoe joint to 750# - held OK. Commenced drilling 7 7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED TH.	P. The	The Del.	TITLE _	Senior	Production	Clork	DATE_	March 17,	1978

TITLE

DATE

APPROVED BY ____

CONDITIONS OF APPROVAL, IF ANY: