

RECEIVED

Form C-103 SRM 1216
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

API 30-015-22398

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Perry R. Bass 3. Address of Operator Box 2760, Midland, Texas 79702 4. Location of Well UNIT LETTER J , 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 20 TOWNSHIP 21S RANGE 28E NMPM.	7. Unit Agreement Name Big Eddy Unit 8. Farm or Lease Name Big Eddy Unit 9. Well No. 60 10. Field and Pool, or Wildcat Undes, Bone Springs
15. Elevation (Show whether DF, RT, GR, etc.) 3204.3' GL 3222.3' KB	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Plug back

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3-19-78: Spotted 90 sks Class "H" cement w/10# sand/sk plus 6# salt/sk & 3% CFR. Yield 1.18/sk. Plug from 12,162' back to 11,920'.
- 3-23-78: Spotted 105 sks Class "H" cement w/10# sand/sk plus 3# salt/sk and 5% CFR. Slurry weight: 17.4 PPG. Plug from 11,370' back to 11,170'.
- 3-27-78: Spotted 50 sks Class "H" cement from 10,700' back to 10,600'.
Spotted 50 sks Class "H" cement from 9,600' back to 9,500'.
Spotted 50 sks Class "H" cement from 7,700' back to 7,600'.
- 3-28-78: Spotted 100 sks Class "H" cement from 7,000' back to 6,838'. Strapped DP in hole. Tagged TOC @ 6,838'. Rigging up to run 5 1/2" casing.
- 10.1 PPG mud between plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. J. Wertz, Jr. TITLE Senior Production Clerk DATE April 7, 1978
APPROVED BY W. A. Gessett TITLE SUPERVISOR, DISTRICT II DATE APR 11 1978
CONDITIONS OF APPROVAL, IF ANY: