

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>C. E. Lague + B. N. Munn</u>		Lease <u>Wanda</u>		Well # <u>1</u>	
Location of Well	Unit <u>2185N 330W</u>	Section <u>9</u>	Township <u>21</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Co Tools</u>	Type of Equipment <u>Rotary Lariat 2-9-78</u> <u>2-20-78</u>				
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 7/8</u>	<u>7" 8 5/8" 13 3/8"</u>	<u>20 24 48</u>		<u>500</u>	<u>1300 circ.</u>
<u>7 7/8" 6 1/4"</u>	<u>4 1/2" 4 1/2" 5 1/2"</u>	<u>10.5 10.5 15.5</u>		<u>2500</u>	<u>540 circ</u> <u>275</u>
Casing Data:					
Surface <u>15</u> joints of <u>7"</u> inch <u>20</u> # Grade <u>J-55</u> (Approved) (Rejected)					
Inspected by <u>M.S.</u> date <u>2-22-78</u>					
Cementing Program					
Size of hole <u>9 7/8</u> Size of Casing <u>7"</u> Sacks cement required <u>200</u>					
Type of Shoe used <u>guide</u> Float collar used <u>No</u> Btm 3 jts welded <u>No</u>					
TD of hole <u>500'</u> Set <u>503'</u> Feet of <u>7</u> Inch <u>20</u> # Grade <u>J-55</u>					
New-used csg. @ <u>503'</u> with <u>200</u> sacks neat cement around shoe					
+ <u>1</u> sack additives <u>270 c.c.</u>					
Plug down @ <u>12:15</u> (AM) (PM) Date <u>2-23-78</u>					
Cement circulated <u>No</u> No. of Sacks					
Cemented by <u>Dowell</u> Witnessed by <u>Mike Stubblefield</u>					
Temp. Survey ran @ <u>9:30</u> (AM) (PM) Date <u>2-23-78</u> top cement @ <u>27'</u>					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>to shallow water at 95'</u>					

P4A

1. Run 50 sk Plug @ 2205-2405.
2. Run 35 sk Plug @ 1950-1850 - No results
3. Run 35 sk plug @ 1655-1555
4. Run 35 sk plug @ 914-814
5. Run 35 sk plug @ 450-550
6. Run 10 sk plug @ surface.

witnessed by BW weaver