

NMOC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM - 06750

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Perry R. Bass ✓

3. ADDRESS OF OPERATOR

Box 2760, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 1980' FWL of Section 15 - Unit letter K.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3414' GL

3432' KB

7. UNIT AGREEMENT NAME

Big Eddy Unit

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

61

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 15, T21S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

RECEIVED

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud date & surface casing XX

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clear and concise details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded 15" hole @ 11:00 AM (CDT), May 30, 1978.

Drilled to 406'. Ran 10 jts 11 3/4", 42#, H-40, ST&C casing. Set @ 406'. Cemented with 300 sks Class "C" + 2% CaCl₂ + 1/2# Flocele per sk. Plug down @ 2:00 AM (CDT), May 31, 1978. Circulated out 50 sks. WOC 13 hours. Tested BOPE & casing to 1000# - held OK. Drilled float joint - no cement. Drilled guide shoe & 5' new hole (11"). Tested formation to 500# - bled to zero in 10 min. Ran cement bond - GR - collar locator log. With drill pipe @ 350' squeezed with 100 sks Class "C" Thickset. WOC 13 1/2 hours - tagged cement @ 355'. Drilling 11" hole with full returns.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Murty, Jr.

TITLE

Senior Production Clerk

DATE June 6, 1978

(This space for Federal or State office use)

APPROVED BY

Albert R. Hall

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 08 1978

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones; or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.