FRACTURE TREAT

REPAIR WELL

(Other)

SHOOT OR ACIDIZE

N. M. O. C. C. COPY

UNITED STATES DEPARTMENT F THE INTERIOR (Other Instructions of verse side)

SUBMIT IN TRIPLIC

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug back, run casing

Budget Bureau No. 42-R1424, 5. LEASE DESIGNATION AND SERIAL NO.

NM - 02295

GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

ALTERING CASING

ABANDON MENT

Capy to 87

	Use "APPLICATION FOR PERMIT—" for such proposals.)	
1.	OIL WELL X OTHER RECEIV	7. UNIT AGREEMENT NAME
2.	NAME OF OPERATOR	8. FARM OR LEASE NAME
3.	Southland Royalty Company ADG 18 197	Trigg-Federal
·	1100 Wall Towers West, Midland, TX 79701	1
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements. U. C. See also space 17 below.) ARTESIA, OFFICE ARTESIA, OFFICE	10. FIELD AND POOL, OR WILDCAT
	1980' FNL & 2230' FWL	11. SEC., T., B., M., OR BLK. AND SUBVEY OR AREA
		Sec. 3, T-20-S, R-27-E
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	3341.0' GR	Eddy New Mexico
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or O	ther Data
	NOTICE OF INTENTION TO: SUBSEQUE	ENT REPORT OF:
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIEE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 7 7/8" hole to TD of 10,970'

Ran Schlumberger Compensated Neutron-Formation Density and Dual Laterlog

Spot 60 sx Class "H" cement 10,315-10,515' (8-1-78). Spot 60 sx Class "H" cement 9,160-9,255' (8-1-78).

Dress off cement plug, w/7 7/8" bit to 9,160.

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

Ran 4 1/2" 11.6# S-95, K-55, N-80 csg set 0 9089'.

Cement w/ 575 sx Class "H" cement w/0.5% CFP-2 & 5# KCl/sx.

Plug down @ 11:15 p.m. 8-1-78. MOR.

T/cement by temperature survey @ 7120'.

Will test csg w/completion riq. Notified USGS prior to spotting cement plugs. AUG 7 1978
U.S. GEULUGIUAL SUIVEY
ARTERIA MEW MEXICO ARTESIA, NEW MEXICO

8. I hereby certify that the foregoing is true and correct		
SIGNED C. Harvey Can	THILE District Engineer	DATE 8-3-78
(This space for Federal of State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE ACTING DISTRICT ENGINEER	DATE AUG 1 7 1978