

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

APR 10 1979

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☒	OTHER ☐
Name of Operator <u>PERRY R. BASS</u>		
Address of Operator <u>Box 2760, MIDLAND, TEXAS 79702</u>		
Location of Well UNIT LETTER <u>C</u> , <u>1980</u> FEET FROM THE <u>WEST</u> LINE AND <u>660</u> FEET FROM THE <u>NORTH</u> LINE, SECTION <u>31</u> TOWNSHIP <u>21S</u> RANGE <u>28E</u> N.M.P.M.		

5a. Indicate Type of Lease State ☐ Fee ☒
5. State Oil & Gas Lease No. _____
7. Unit Agreement Name <u>BIG EDDY UNIT</u>
8. Farm or Lease Name <u>BIG EDDY UNIT</u>
9. Well No. <u>65</u>
10. Field and Pool, or Wildcat <u>UNDESIGNATED - EAST CARLSBAD MORAHO</u>
12. County <u>EDDY</u>

15. Elevation (Show whether DF, RT, GR, etc.)

3131.4' GL 3149' KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK	☐
TEMPORARILY ABANDON	☐
OR ALTER CASING	☐
OTHER	☐

PLUG AND ABANDON	☐
CHANGE PLANS	☐
OTHER	☐

REMEDIAL WORK	☐
COMMENCE DRILLING OPNS.	☐
CASING TEST AND CEMENT JOBS	☐
OTHER	☒

ALTERING CASING	☐
PLUG AND ABANDONMENT	☐
OTHER	☒

Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

DRILLED 11" HOLE TO 2890'.

RAN 15 JTS 8 5/8", 28", S-80, STAC AND 56 JTS 8 5/8", 24", K-55, STAC CASING PLUS FLOAT SHOE AND COLLAR. SET AT 2890'. DV TOOL AT 1164'. FIRST STAGE CEMENT: 300 SKS HOWCO "KITE" PLUS ADDITIVES - TAILED W/200 SKS CLASS "C" PLUS ADDITIVES. PLUG DOWN AT 8:30 AM, MARCH 13, 1979. SECOND STAGE CEMENT: 200 SKS HOWCO "KITE" PLUS ADDITIVES - TAILED W/100 SKS CLASS "C". PLUG DOWN AT 1:45 PM - CIRC. OUT 26 SKS. WOC 16 HOURS. YELLOWJACKET TESTERS TESTED BORE + CHOKER MANIFOLD TO 5000# - TESTED OK. TESTED HYDRIL TO 1500# - HELD OK. DRILLED DV TOOL, FLOAT COLLAR, CEMENT, SHOE AND 5' NEW HOLE. TESTED SEAT TO 1000# - HELD OK. DRILLING 7 7/8" HOLE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

H. J. Murthy, Jr.

TITLE

Sr. Prod. Clerk

DATE

Apr. 9, 1979

APPROVED BY

W. A. Gressett

TITLE

SUPERVISOR, DISTRICT II

DATE

APR 11 1979

CONDITIONS OF APPROVAL, IF ANY: