
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

David L. Davis TITLE SR. PETROLEUM ENGINEER DATE June 7, 1979

Tests to be filed with the appropriate district office or the Commission must be filed within 30 days after the completion of any new, drilled or reamed well. It shall be accompanied by the copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall be reported. For multiple completions, items 3a through 3d shall be reported for each zone. The form is to be filed in quadruplicate except on the land where six copies are required, see Rule 11.5.

Northwestern New Mexico

Southeastern New Mexico

[illegible]

From	To	Thickness in Feet	Formation
0	728	728	SAND & Red Lodic
178	2884	2156	ANY
1784	3432	548	ANY
1732	4868	1436	LM, SH & DOLO
1868	5822	954	LM & DOLO
5822	6517	695	SB & LM
6517	7894	1377	LM, SB & DOLO.
7894	10635	2741	LM
7894	10973	338	LM & SH
10635	11017	44	SH
10973	12108	1091	LM & SH
0	728	728	SAND & Red Lodic
178	2884	2156	ANY
1784	3432	548	ANY
1732	4868	1436	LM, SH & DOLO
1868	5822	954	LM & DOLO
5822	6517	695	SB & LM
6517	7894	1377	LM, SB & DOLO.
7894	10635	2741	LM
7894	10973	338	LM & SH
10635	11017	44	SH
10973	12108	1091	LM & SH
No. 1 From None to None			
IMPORTANT WATER SANDS			
No. 1 From None to None			
OIL OR GAS SANDS OR ZONES			
No. 1 From 10,630' to 10,675 (STRA)			
FORMATION			