

NM
Page 43

TI 12 100'; FBD 12,300'; Complete
POINT GAUGES:

FOUR POINT GAUGES:
1.25" orif

FOUR POINT GAUGES:
Flwd 550 MCF/GPD, 1.25" orifice, 60 mins.
TP 2543# (NR), 60 mins, TP 1
Flwd 550 MCF/GPD, chk (NR), 60 mins, TP 1
Flwd 550 MCF/GPD, (NR), 60 mins, TP 1

Flwd 550 MCFGPD, 1.25
TP 2543#
Flwd 739 MCFGPD, chk (NR), 60 mins, TP 1897
Flwd 807 MCFGPD, chk (NR), 60 mins, TP 1897
Flwd 154 MCFGPD, chk (NR), 60 mins, TP 1897
TPRS: Salt 450', Base Salt 2415', Base
2663' Wolfcamp 9740'.

Flwd 753 MC:GPD, chk (NR), 60 mics, 11,377'
Flwd 807 MC:GPD, chk (NR), 60 mics, 11,377'
Flwd 754 MC:GPD, chk (NR), 60 mics, 11,377'
LOG TOPS: Salt 450', Base Salt 2415', Bone Spring 2794', Bone Spring 6362', Wolfcamp 9740',
2794', Bone Spring 6362', Middle Morrow 11,377',
11,377', Avoka 11,377', Barnett 12,695'

LOGS RAIL, Bone Spring 11,377', Middle Morrow
2794', Avoka 11,015', Barnett 12,695'
Lower Morrow 12,448',
LOGS RAIL, CNL, FDC, DILL, MICL
ISSUED

Lower Morrow 12,448', Barnes
LOGS RUN: CNL, FDC, DILL, MICL
COMPLETION ISSUED

5-19-79

5-3-21 NM
IC 30-015-70300-72