

NM.O.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other Instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-17200

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

MAY 15 1979

2. NAME OF OPERATOR

Harvey E. Yates Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1933, Roswell, New Mexico 88201

O. C. C.
ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 660' FNL & 660' FEL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Southeast Indian Basin

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indian Basin

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 23, T-22S, R-23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4141.5' GL

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Spud, run surface casing X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-20-79 Spudded 17 1/2" hole at 4:00 PM.

4-23-79 Depth 300'. Ran 12 Joints (311') 13 3/8" OD 48#, H-40, 8Rd, ST&C casing and set at 300' RTM. Cemented with 300 Sx Class C w/2% CaCl. Plug Down at 1:30 AM 4-24-79. Circulate est. 35 Sx.

4-24-79 After 18 hrs WOC, tested casing and BOP to 500 psi for 30 min. OK.

RECEIVED
MAY 11 1979
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Paul Harder

TITLE Engineer

DATE 5-9-79

(This space for Federal or State office use)

APPROVED BY

Lee S. Lara

TITLE ACTING DISTRICT ENGINEER

DATE MAY 14 1979

CONDITIONS OF APPROVAL, IF ANY: