

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42 R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM-17200

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole DEC 4 - 1979

2. NAME OF OPERATOR Harvey E. Yates Company

3. ADDRESS OF OPERATOR P. O. Box 1933, Roswell, N. M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface 660' FNL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
4141.5' GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Southeast Indian Basin

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indian Basin

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T-22S. R-23E

12. COUNTY OR PARISH 13. STATE

Eddy

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-13-79 Well was plugged and abandoned as follows:

1. A 5 1/2" CIBP was run on wireline and set at 2610' and 35' of cement was placed on top CIBP w/wire line bailer.
2. 5 1/2" casing was shot off w/jet cutter at 2402'. LD casing.
3. A 60 Sx Cl H cement plug was spotted at 2452' (50' inside 4 1/2" casing stub) back to 2230' (50' into 8 5/8" casing at 2288') 222' plug.
4. A 15 Sx Cl H cement plug was placed from 49' to surface. 10#/gal mud was placed between plugs.

A plate was welded across 8 5/8" casing stub and a 4" pipe dry hole marker was installed. P & A 11-15-79.

RECEIVED

DEC 3 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 11-29-79

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

TITLE AGING DISTRICT ENGINEER

DATE DEC 03 1979

CONDITIONS OF APPROVAL, IF ANY: