

FD-321
(2-7-79)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1. ICATED
(Other 2. directions on re-
verse side)Form approved.
Budget Estimate No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
WM 55039 055038
6. IF IN HAN, ALLOTTEE OR LEASE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for a directional drill or a plug or plug back to a different reservoir.
It is for such requests.)

1. OIL WELL ☐ GAS WELL ☒	AUG 1 1979		7. UNIT / ELEMENT NAME Big Eddy Unit
2. NAME OF OPERATOR W. C. Blanks	O. C. C. ARTESIA, OFFICE		8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR 302 Building of the Southwest, Midland, Texas 79701			9. WELL NO. 67
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. Specify space 17 below.) At surface 1980' FSL and 990' FWL			10. FIELD AND POOL, OR WILDCAT Wildcat - Atoka
			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 15, 21S, 30E
14. PERMIT NO.	15. ELEVATION (Show whether FF, RT, GR, etc.) 3265.2' GL 3281' KB	12. COUNTY OR PARISH Eddy	13. STATE New Mexico
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACURE TREAT ☐	MULTIPLE COMPLETION ☐	FRACURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒ XXX	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	
(Other) ☐			
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
17. DISCLOSE PROPOSED OR COMPLETED OPERATIONS (Check), state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			

PROPOSED PLUGGING PROGRAM (AFTER PLUG BACK OPERATION: SEE 9-331C DATED 5-4-79).

1. Set a 100' cement plug from 3550 - 3650' KB (10 3/4" casing set at 3600' KB).
2. Set a 100' cement plug from 1140 - 1240' KB.
3. Set a 10' cement plug from surface to 10' below ground level.
4. Prepare and install P/A marker.
5. Restore surface as required by BLM.

NOTE -- Verbal approval received prior to operations.

RECEIVED

JUL 23 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Consultant

DATE 7-19-79

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) ALBERT A. STALL

TITLE ACTING DISTRICT ENGINEER

DATE JUL 31 1979

CONDITIONS OF APPROVAL, IF ANY: