

NMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other Instructions
verse side)FE-
re-Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 020 7950

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ross Federal Comm.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cemetery Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T-21-S, R-24-E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐ Drilling Well

2. NAME OF OPERATOR

DAVID FASKEN

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL. (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

3300' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3761' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Intermediate Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-19-78 to 12-27-78 drilled 12-1/4" hole with fresh water from 395' to 3000' --- full mud returns with minor seepage.
- 12-27-78 set 8-5/8" casing @ 3000' (11 jts., 435.26', K-55, 32#/Ft., LT&C and 65 jts., 2552.50', K-55, 24#/Ft., ST&C.).
- 12-27-78 cemented 8-5/8" casing with 900 sacks Halliburton Lite with 1/4# Flocele per sack and 2% CaCl, S.W. 18.1#/gal. + 200 sacks Class "C" with 2% CaCl, S.W. 14.8#/gal. plug down at 1:45 P.M., C.S.T., circulated 28 bbls. or 93 sacks excess cement.
- W.O.C. 20-1/2 hours, set slips, cut off, and N.U. B.O.P.'s.
- 12-29-78 drilling ahead at 3535', 7-7/8" hole.

RECEIVED

JAN 2 - 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

(This space for Federal or State office use)

TITLE Agent

DATE 12-29-78

APPROVED BY

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 5 1979

CONDITIONS OF APPROVAL, IF ANY: