

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 020 7950

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ross Federal Comm.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cemetery Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T-21-S, R-24-E

12. COUNTY OR PARISH

13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER **Drilling Well**

2. NAME OF OPERATOR

DAVID FASKEN

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, TX

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

3330' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3761' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Production casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 7-7/8" hole to TD of 9848' between 12-29-78 & 1-25-79.
2. Jan. 15, 1979, DST No. 1 9418'-9485' (See attached).
3. Jan. 22, 1979, DST No. 2 9490'-9600' (See attached).
4. Jan. 24, 1979, DST No. 3 9600'-9735' (See attached).
5. Jan. 25, 1979, Open hole logs CNL-FDC, & DLL.
6. Jan. 27, 1979, RIW w/one float shoe (1.66') + one float collar (1.45') + 11 jts (421.88') Ruff-koted 4 1/2" N-80 11.60#/ft LT&C csg from 9766' up to 9344' + 233 jts 4 1/2" N-80 & J-55 11.60#/ft LT&C csg (9418.29') + one csg marker (4.30') on top of Ruff-koted @ 9340' = 9847.58' w/csg shoe set @ 9845' KB. Cemented w/800 sx Class "H" w/5# KCl/sk & 0.8% Halad-22, SW 15.7#/gal (Yield: 1.18 cf/sk). Good mud returns, plug down @ 5:15 p.m. 1-26-79. Set slips, cut off 4 1/2" csg & NU wellhead.
7. Jan. 28, 1979, RD rotary tools, ran temperature survey. Top of cement on back side of 4 1/2" csg is @ 7300'. PBSD is @ 9759'.

18. I hereby certify that the foregoing is true and correct

SIGNED *Robert H. Angevine*
Robert H. Angevine

TITLE Agent

DATE 2-2-79

(This space for Federal or State office use)

APPROVED BY *Joe L. Lara*

TITLE

ACTING DISTRICT ENGINEER

DATE

FEB 12 1979

CONDITIONS OF APPROVAL, IF ANY: