

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN DUPLICATE*
(Other instructions on re-
verse side)Copy to 87
Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0207958

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shell Federal Comm.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cemetery Morrow Gas

11. SEC., T., R., M., OR BLK. AND

SURVEY OF AREA
Sec. 5, T-21-S,
R-24-E.

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling well

NOV 14 1978

2. NAME OF OPERATOR

David Fasken ✓

3. ADDRESS OF OPERATOR

608 First National Bank Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FWL and 3300' FSL.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3765.7' Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Set & cement 13-3/8" csg ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 17½" hole @ 4:00 p.m. 11-1-78.
2. Drilled 17½" hole to 400' with full mud returns.
3. Set 13-3/8", J-55, 54.50#/ft, 8rd ST&C @ 400'.
4. Cemented 13-3/8" w/400 sx Halliburton Lite w/½# flocele/sk and 2% CaCl (SW 13.6#/gal) and 200 sx Class "C" w/2% CaCl (SW 14.8#/gal), plug down 5:45 a.m. 11-3-78, circulated 55 bbls cement = 201 sx.
5. 11-3-78 W.O.C. and N.U. B.O.P.'s.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

TITLE Agent

DATE 11-6-78

(This space for Federal or State office use)

(Orig. Sgd.) ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

NOV 13 1978

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

DATE