

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0207958

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shell Federal Comm.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Cemetery Morrow Gas

11. SEC. T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 5, T-21-S, R-24-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL ☐ GAS ☐  
WELL WELL OTHER ☒ Drilling Well

2. NAME OF OPERATOR

David Fasken

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, TX 79701 O.C.C.  
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

660' FWL &amp; 3300' FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3765.7 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Set &amp; cement 8-5/8" casing

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-4-78

2:00 a.m. Drilling 12 1/4" hole @ 18' per hour in line with full mud returns.

11-4-78 to 11-10-78

Drilling 12 1/4" hole in line with full mud returns from 400' to 3000'.

11-10-78

Set 8-5/8" casing @ 3000', 16 jts (628.12') K-55 32#/ft LT&amp;C and 60 jts (2379.37') K-55 24#/ft ST&amp;C. Cemented with 925 sx Halliburton Lite with 1/4# flocele per sack &amp; 2% CaCl (S.W. 13.1 to 13.6 P.P.G.) and 200 sx Class "C" with 2% CaCl (S.W. 14.8 P.P.G.) Circulated 37 bbls or 123 sacks excess cement, P.D. 5:45 a.m. C.S.T. on 11-10-78--Cementing operation monitored by Mr. James Brasfield, U.S.G.S.

11-11-78

W.O.C. until 3:45 a.m. (11-11-78) or 22 hours, drilling ahead in line with 7-7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

TITLE Agent

DATE 11-13-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE NOV 15 1978